
# Project purpose and need

### Why are improvements being planned?

- To improve safety and mobility.
  - In peak periods, congestion at the ramp intersections can cause traffic queues to extend back onto I-15, potentially leading to severe crashes.
  - Congestion at the ramp intersections increases delay at the nearby frontage road intersections, which are projected to operate at level of service (LOS) F with 2042 traffic volumes.
  - The ramps were not designed for the current speed limit of 80 mph. To improve safety, the ramps will be extended to provide adequate acceleration and deceleration lengths.

# Existing and projected traffic

### 2015 traffic



**2,075** vehicles enter the intersections (ramp and frontage road intersections) during the PM peak hour

### Projected 2042 traffic



**3,050** vehicles enter the intersections (ramp and frontage road intersections) during the PM peak hour

42%
increase
in traffic
by 2042

## Intersection alternatives considered

#### SIGNALIZED INTERSECTIONS


The stop sign control at the ramp intersections is replaced with traffic signals and the **overpass is replaced** to add left-turn lane storage. Estimated project cost: **\$8 million** 


Pros	Cons
• Familiar	• Estimated cost exceeds project funding
<ul> <li>Reduces delay for ramp traffic</li> </ul>	<ul> <li>Signals are not currently warranted</li> </ul>
	<ul> <li>Vehicle queues increase delay for</li> </ul>
	frontage road traffic (LOS F in 2042)

#### **ROUNDABOUTS**

The four ramp and frontage road intersections are combined into two single-lane roundabouts and the current **overpass is retained**. Estimated project cost: **\$4 million** 

Pros	Cons
Estimated cost meets project funding	• Less familiar
<ul> <li>Reduces delay for ramp and frontage road traffic compared to all other options</li> <li>Reduces number of crashes and crash severity compared to signalized option</li> <li>Deterrent to wrong-way driving on the</li> </ul>	
off-ramps	






## Intersection alternatives considered

#### SINGLE-POINT URBAN INTERCHANGE (SPUI)

The two ramp intersections are combined into one signalized intersection and the **overpass is replaced**. Estimated project cost: **\$25 million** 

Pros	Cons	
<ul> <li>Increases capacity and reduces delay more than signalized intersections option</li> <li>Deterrent to wrong-way driving on the off-ramps</li> </ul>	<ul> <li>Estimated cost exceeds project funding</li> <li>Less familiar</li> </ul>	




#### **DIVERGING DIAMOND INTERCHANGE (DDI)**

The two ramp intersections are signalized, with the overpass traffic direction switched to eliminate opposing traffic for left-turns to on-ramps, and the **overpass is replaced**.

Estimated project cost: \$15 million


Pros	Cons
<ul> <li>Increases capacity and reduces delay more than signalized intersections option</li> <li>Deterrent to wrong-way driving on the</li> </ul>	<ul> <li>Estimated cost exceeds project funding</li> <li>Less familiar and contrary to driver expectations</li> </ul>
off-ramps	



## Selected intersection alternative

### Roundabouts

- Estimated project cost meets
   program funding other options
   exceed funding
- Expected traffic delays in 2042 for roundabouts (combining the ramp and frontage road traffic in one intersection) is less than other options
- Roundabouts are safer than other options



# Safety of roundabouts

#### **Fewer Crashes**


Intersections converted to roundabouts have shown fewer total crashes (property damage only, injury and fatality) than crashes at two-way stop-controlled and signalized intersections.

From "NCHRP Report 672 – Roundabouts An Informational Guide" (2010)

32%
reduction
in total
crashes

#### Less Severe Crashes

Intersections converted to roundabouts have shown significantly fewer injury and fatality crashes than crashes at two-way stop-controlled and signalized intersections.



# Design features for large trucks

- Roundabout curbs are designed with smooth (rolled) profiles to minimize the disruption to offtracking vehicles.
- Roundabouts have raised truck
   aprons around the center island,
   designed to accommodate the off tracking trailers of large trucks.
- WB-67s and smaller trucks can navigate the roundabouts without off-tracking on the aprons. Larger trucks may need to use the aprons.
- The proposed roundabouts can handle oversize vehicles as long as 150', when utilizing rear steering.

